

Street sweeper

Sweeper for large tractors

Model FF 1700 - 3000 SP

Model FF 2200 - 3000 SP - SPS



- Ø 600 mm poly- or steel brushes
- Heavy duty gear box and duplex chain draw
- Extra heavy duty caster wheels
- Support legs for easy on/off-mounting
- Hydraulic angling with 2 heavy angling cylinders
- Quick mounting/dismounting of the brush roller



Technical data



Swingspeed gearbox for tractors with high PTO speed



Automatic chain tension incl. Duplex chains



Extra heavy puncture free wheels

Model	FF 1700 SP	FF 2000 SP	FF 2200 SP-SPS	FF 2500 SP-SPS	FF 2800 SP-SPS	FF 3000 SP-SPS
Largest width	1910 mm	2210 mm	2410 mm	2710 mm	3010 mm	3210 mm
Largest length *	1170 mm					
Largest height	800 mm					
Sweeping width at total angling	1600 mm	1900 mm	2100 mm	2400 mm	2700 mm	2900 mm
Brush diameter	Ø 600 x 7" mm on floating brush roller mounted in spline axle					
Brush type	Standard with polyester, optional a mix of poly/steel					
Angling - hydraulic	20° right / left - 2 swing cylinders					
Wheels	2 pcs 10 x 3" high-load					
Power requirements	16 kW (21,7 HP)	19 kW (26 HP)	21 kW (28,5 HP)	24 kW (32,5 HP)	27 kW (36,5 HP)	30 kW (40,5 HP)
Weight * FF SP / FF SPS	405 kg	435 / 455 kg	455 / 475 kg	480 / 500 kg	500 / 525 kg	650 / 675 kg

* Length and weight depend on frame type

GMR



GMR maskiner a/s
DK-8700 Horsens
T. +45 75 64 36 11
www.gmr.dk

NESBO A/S
DK-9550 Mariager
T. +45 98 58 44 00
www.nesbo.dk

Dealer: