

Street sweeper

Sweeper - light model
Mechanical operated

Model FF 1200 - 1300 - 1500 LA / LSA



- Mechanical operated
- Hydraulic angling
- Quick mounting/dismounting of the brush roller
- For tractors with 2000 rpm. on PTO we recommend the swing-speed type
- Floating brush roller mounting
- Big puncture proof rubber wheels
- Ø 500 mm poly- or steel brushes
- Heavy storage supporting legs secures the stability



Technical data



Heavy storage supporting legs for quick mounting/dismounting and secures the stability

Model	FF 1200 LA / LSA	FF 1300 LA / LSA	FF 1500 LA / LSA
Largest width	1350 mm	1450 mm	1650 mm
Largest length *	950 mm		
Largest height	650 mm		
Sweeping width at total angling	1125 mm	1225 mm	1425 mm
Brush diameter	Ø 500 x 5" mm on floating suspended brush roller in spline axles		
Brush type	Standard with polyester, optional a mix of poly/steel		
Angling - hydraulic	20° right / left - 1 swing cylinder		
Wheels	2 pcs 8 x 2,5" rubber wheels in revolving forks		
Power requirements	8 kW (11 HP)	9 kW (12 HP)	10 kW (15,5 HP)
Weight *	130 kg	140 kg	150 kg

* Length and weight depend on frame type

GMR



GMR maskiner a/s
DK-8700 Horsens
T. +45 75 64 36 11
www.gmr.dk

NESBO A/S
DK-9550 Mariager
T. +45 98 58 44 00
www.nesbo.dk

Dealer: